

PURE FARM Antique Tractor Weight Classes

5500, 6500, 10500,12500

1. Tractor must be in original condition. As original design and horsepower.
- 2., **no cut or altered** in any pure farm classes.
maximum footprint for 5500 and 6500 is 229 sq.in. (15.5x38=189 sq.in) see chart below
3. Pull in 1st gear or a gear not to exceed **3 MPH.** for **5500 and 6500**
4. No electric fuel pumps
5. Stationary draw bar 18” in height, 24” back from center of rear wheel minimum.
6. Must have stock air cleaner connected
7. Maximum tire size **18.4 10500,12500**
8. Maximum **6 MPH** speed limit **10500,12500**
- 9.Only gasoline,diesel, or l.p. gas permitted
- 10.**Hitch opening must be 3 ¾ to allow the drop sled hook for all tractors**
11. 3 horn rule for all classes

Stock Tractor Weight Classes

4500, 5500 , 6500, 7500, 8500

1. **Top Cut tires permitted in all classes** maximum footprint for 5500 and 6500 is 229 sq.in. (15.5x38=189 sq.in) maximum footprint is 350 sq.in. for 7500 and 8500 is 229 sq.in. (18.4x 38=325 sq.in)

2. Maximum **4 MPH** speed limit (any gear)
3. Stationary draw bar 18" in height maximum, 18" back from center of rear wheel minimum. 7500 and 8500 classes are 20 inch hitch maximum height
4. Only gasoline, diesel, or l.p. gas permitted
5. **Hitch opening must be 3 ¾ to allow the drop sled hook for all tractors**
6. 3 horn rule for all classes

Open Tractor Weight Classes 4500, 5500, 6500

1. Maximum tire size 18.4
2. Any Cut tires permitted in all classes
3. No RPM limit (unchecked)
4. Maximum 6 MPH speed limit (any gear)
5. Stationary draw bar 20" in height maximum, 18" back from center of rear wheel minimum.
6. Wheelie bars are mandatory.
7. Kill switch required.
8. 3 horn rule for all classes
9. **Hitch opening must be 3 ¾ to allow the drop sled hook for all tractors**

9500/10000 tractors weight classes

1. speed limit 8 mph
2. 18.4 x 38 tires top cuts
3. Stationary draw bar 20" in height maximum, 18" back from center of rear wheel minimum.
4. Wheelie bars are mandatory.
5. Kill switch required.
6. **Hitch opening must be 3 ¾ to allow the drop sled hook for all tractors**

ADDITIONAL RULES FOR ALL CLASSES

1. Tractor must be operated safely at all times, with driver remaining in seat while pulling.
2. Club is not responsible for personal injury, accidents, or damage to tractor or equipment while on grounds.
3. Recommended that all tractors be equipped with a fire extinguisher.
4. Only Gasoline, diesel, or L.P. gas permitted.
5. Must have a twisted clevis or a hitching plate for hookup ,no straight clevises permitted.

6. No dual wheels, tire chains, steel wheels, or four wheel drive tractors.

7. All tractors must weigh in before and after each pull.

8. Front weights cannot exceed 11' front center of rear wheel; rear weights should not exceed rear tires in excess.

9. No more than two pulls per tractor per class. Only one place awarded per tractor per class.

10. The tractor tires must stay inside track boundaries at all times during the pull.

11. No jerking of sled.

Tire footprint chart

11.28 x 38 – 120 sq. in. 12.4 x 38 -140 sq. in. 13.6 x 38 – 168 sq. in. 11.2 x 36 -115 sq. in. 12.4 x 36 -135 sq. in. 14.9 x 28 – 170 sq. in. 18.4 x 28 – 126 sq. in. 13.6 x 28 – 145 sp. in. 13.6 x 24 -130 sq. in. 14.9 x 26 -144 sq. in. 14.9 x 38 -200 sq. in. 18.4 x 34 – 284 sq. in. 18.4 x 38 – 325 sq. in. 15.5 x 38 – 189 sq. in. 16.9 x 38 252 sq. in. 16.9 x 34 – 229 sq. in. 18.4 x 28 – 250 sq. in. 20.8 x 34 – 335 sq. in. 20.8 x 38 – 375 sq. in.