

LAWN STOCK Garden Tractor Rules

LAWN STOCK CLASSES: 12 HP AND UNDER -900# - 950#

16 HP AND UNDER - 1000#-1050#

1. STOCK BORE +.030 OVER
2. STOCK OEM PARTS ONLY OR AFTER MARKET THAT IS EQUIVALENT TO OEM.NO RECAST HEADS.ALLOW ANY 5.300 CONNECTING ROD.
3. HEAD MILLING IS PERMITTED (FLAT), NO WELDING OR ALTERING THE HEAD, MUST BE STOCK HEAD, NO RELIEVED BLOCKS. PORT AND POLISH NOT ALLOWED.
4. SINGLE CYLINDERS ONLY, UNLESS TRACTOR CAME FROM OEM W/TWIN, HAS TO BE UNDER 16HP.
5. 4000 RPM'S MAX. MUST BE CONTROLLED BY MECHANICAL GOVERNOR.
6. CARBURETOR SHALL BE NO LARGER THAN STOCK 30 CARB. W/1" VENTURI. NO SPACERS OR VELOCITY STACKS ALLOWED. MUST BE OEM CARBURETOR. MAY USE 5/8" RING TO ALLOW FOR AFTER MARKET AIR FILTER.
7. OEM FACTORY IGNITION SYSTEM. CHEVY POINTS ALLOWED.
8. MUST HAVE MUFFLER OR VERTICAL EXHAUST.
9. MUST HAVE STOCK OEM FLYWHEEL AND SHIELD. CLUTCH MUST BE SHIELDED.
10. PUMP GAS ONLY, 93 OCTANE MAX. ALLOWED E85 PUMP GAS.NO ADDITIVES OR ALCOHOL ALLOWED.
11. OPEN OR LOCKED REAR ENDS PERMITTED. MAY ALLOW GEAR CHANGES.
12. TIRE SIZE MAX. 23x10.50x12, ALUMINUM WHEELS ALLOWED.TIRES CAN BE CUT OR ALTERED IN ANY WAY. NO PROFESSIONAL PULLING TIRES. 10.50 IN. WIDE WHEEL MAXIMUM.
13. 13" HITCH HEIGHT.
14. STOCK WHEEL BASE, W/OEM TRACTOR FRAME. MAY ALLOW FOR LARGER FLYWHEEL. SHEET METAL CHANGES ALLOWED, BUT MUST RESEMBLE AN OEM TRACTOR. IF TRACTOR CAME WITHOUT FENDERS YOU MUST PUT FENDERS ON. IF TRACTOR CAME W/FENDERS THAY MUST BE THE OEM FENDERS ON THAT TRACTOR. MUST HAVE FOOT RESTS.

15. ENGINE MAY BE REPLACED WITH ANOTHER ENGINE THAT MEETS STOCK CLASS RULES.

16. AFTER MARKET ALUMINUM STARTER PULLEY ALLOWED. MUST HAVE BOLT/WASHER RETAINER ON CRANK END. NO STEEL FRONT PULLY ALLOWED. 7 1/2 INCH X 1 INCH ALUMINUM PULLEY.

17. CAM SHAFTS WITH 218° OF MAXIMUM DURATION WITH 324 LIFT MAX.

18. FRONT WEIGHTS CANNOT EXCEED MORE THAN 72" FROM END OF WEIGHTS TO CENTER OF REAR AXLE.

19. NO ROTARY FUEL PUMPS ALLOWED. CHECKER OR VIBRATOR FUEL PUMP ALLOWED.