

STOCK GARDEN TRACTOR RULES.

STOCK CLASSES: 10 HP AND UNDER - 1000 # -1050#

1. STOCK BORE +.030 OVER
2. CAMSHAFT .330 LIFT MAX AT VALVES
3. STOCK VALVE DIMENSIONS, STAINLESS STEEL VALVES ALLOWED.
4. FOUR BOLT RODS ALLOWED.
5. NO CRANKSHAFT STROKING OR POP UP PISTONS, PISTON CAN NOT POP OUT ABOVE BLOCK, STEEL CRANKS ALLOWED.
6. NO REVERSE PORT ENGINES.
7. HEAD MILLING IS PERMITTED, NO WELDING OR ALTERING THE HEAD, MUST BE STOCK HEAD, NO RECAST OR BILLET HEADS ALLOWED, NO RELIEVED BLOCKS, PORT AND POLISH ALLOWED, CAN CLEAN UP AROUND VALVE AREA BUT CAN NOT GO INTO CYLINDER.
8. SINGLE CYLINDERS ONLY.
9. CARBURETOR SHALL BE NO LARGER THAN STOCK 30 CARB. W/1" VENTURI. NO SPACERS OR VELOCITY STACKS ALLOWED. MUST BE OEM CARBURETOR.
10. OEM FACTORY IGNITION SYSTEM, CHEVY POINTS ALLOWED, ELECTRONIC IGNITION ALLOWED.
11. FLYWHEEL, MUST HAVE 1/8" STEEL OR 3/16" ALUMINUM ALL THE WAY AROUND. STEEL CAN RUN STOCK SHIELD. STEEL FLYWHEEL REQUIRED!
12. OEM MANUFACTURED BLOCKS ONLY.
13. PUMP GAS, RACING GAS OR ALCOHOL ALLOWED. NO ADDITIVES ALLOWED.
14. OPEN OR LOCKED REAR ENDS PERMITTED.
15. TIRE SIZE MAXIMUM OF 26X12X12, CUT TIRES AND ALUMINUM WHEELS ALLOWED.
16. 13" HITCH HEIGHT.
17. 52" WHEEL BASE, W/OEM STYLE TRACTOR FRAME.

18. DRIVER MUST WEAR "DOT" APPROVED HELMET.
19. ENGINE MUST HAVE SCATTER SHIELD ON STARTER SIDE, ON INLINE CONCEPT.
20. FRONT CRANKSHAFT MUST HAVE RETAINER BOLT AND WASHER IF RUNNING WITH STARTER PULLEY.
21. FIRE SUIT REQUIRED!