

8000 WORK STOCK DIESEL TRUCKS

8000LBS WEIGHT IS WITH DRIVER

BALLAST IS PERMITTED. **HANGING FRONT WEIGHTS ARE ALLOWED.** BALLAST MAY BE ADDED IN THE BED OF THE TRUCK. IF USED MUST BE SECURELY FASTENED TO THE BED ONLY. ADDING WEIGHT IN OTHER AREAS OF THE TRUCK WILL RESULT IN A DISQUALIFICATION.

THE BODY & TRUCK BED MUST BE THE OEM TRUCK BODY INCLUDING THE FULL BED

FOUR-WHEEL HYDRAULIC BRAKES ARE MANDATORY

MUST HAVE FACTORY OEM BUMPERS FRONT

OEM CHASSIS IS MANDATORY

DRIVELINE ONE-TON OR SMALLER

ENGINE STOCK APPEARING OEM

EXHAUST MUST EXIT UP-WARD

FUEL NO NITROUS OXIDE OR PROPANE

FUEL INJECTION PUMP STOCK- APPEARING

OEM FUEL TANK

ENGINES TURNING 4500 RPM AND HIGHER MUST BE EQUIPPED WITH A HARMONIC BALANCER OR DAMPER

HITCH MAX 26 INCHES

NO HAND-THROTTLES

TIRES MUST RUN DOT STREET TIRES, NO CUT ,DUAL TIRES ARE PERMITTED AS LONG AS IT CAME FROM FACTORY WITH THEM ON IT

SINGLE TUNER IS PERMITTED

TURBOCHARGER IS LIMITED TO A STOCK-APPEARING OEM/FACTORY
CHARGER ONLY
MUST HAVE VALID DRIVERS LICENCES

Must be street legal